| Specifiche | VLT 100 | VLT 100-NC | VLT 60 |
|---|---|---|---|
| Range in temperatura | -40ºC to -85ºC | -40ºC to -100ºC | -20ºC to -60ºC |
| Temperature Display | LED | | N/A |
| Compressore | 2; ognuno da 1/4 HP | | 1; 1/4 HP |
| Cooling Capacity: | 150 Watts @ -40ºC<br>120 Watts @ -60ºC<br>70 Watts @ -80ºC | | 75 Watts @ -20ºC<br>0 Watts @ -60ºC |
| Standard Cooling Probe | 3 in. Rigid Coil | | 1.5 in. Rigid Coil |
| Optional Cooling Probes | Cold Finger<br>Flexible | | None |
| Dimensioni<br>h x w x d | 53.3 x 38.1 x 51.1 cm | | 22.9 x 25.4 x 27.9 cm |
| Peso | 84.2 kg | | 22.3 kg |
| Alimentazione | 240V, 50/60 Hz, 6A | | 240V, 50 Hz, 2.5A |
| Probe Style / Cat. No | 3 In. Rigid Coil / P85C6A102E<br>Cold Finger / P85C8A102E<br>Flexible / P85C4A102E | 3 In. Rigid Coil / P10N6A102E<br>Cold Finger / P10N6A102E<br>Flexible / P10N4A102E | 1.5 In. Rigid Coil / 07096 |

**Distributori esclusivi per l'Italia**
***TQ Technologies for Quality Srl***
mail: info@tqsrl.com Tel: 0104070991

| | Insulated Flexible Hose | 3 In. Rigid Coil Probe (VLT 100, KR 80) | 1.75 In. Rigid Coil Probe (VLT 60) |
|---|---|---|---|
| Diametro | VLT 100 - (7.14 cm)<br>VLT 60 - (3.81 cm)<br>KR Series - (3.81 cm) | (7.62 cm) | (4.44 cm) |
| Lunghezza | VLT 100 - (1.83 m)<br>VLT 60 - (1.22 cm)<br>KR Series - (1.22 m) | (38.1 cm) exposed length; (22.2 cm) Coil length | (38.1 cm) exposed length; (19.05 cm) Coil length |

**Rigid coil**

| | 1.5 In. Rigid Coil Probe (VLT 60) | Cold FInger Probe (VLT 100) | Flexible Probe (VLT 100) |
|---|---|---|---|
| Diametro | (3.81 cm) | (1.91 cm) | (1.59 cm) |
| Lunghezza | (38.1 cm) exposed length; (11.4 cm) Coil length | (30.48 cm) | (38.1 cm) |

**Cold finger**

**Flexible probe**

**Distributori esclusivi per l'Italia**
***TQ Technologies for Quality Srl***
mail: info@tqsrl.com Tel: 0104070991