



**Analogico 2 litri: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
9.9 x 10.9 x 14 cm  
Dimensioni (L x W x D):  
25.9 x 20.3 x 30 cm

**Analogico 2 litri basso: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
12.7 x 27.4 x 4.8 cm  
Dimensioni (L x W x D):  
26.9 x 34.5 x 30.4 cm

**Analogico 5 litri: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
12.7 x 27.4 x 14 cm  
Dimensioni (L x W x D):  
26.9 x 34.5 x 30.4 cm

**Analogico 10 litri: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
26.9 x 29.5 x 14 cm  
Dimensioni (L x W x D):  
42.4 x 37.6 x 30 cm



**Analogico 20 litri: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
24.1 x 44.5 x 12.7 cm  
Dimensioni (L x W x D):  
41.5 x 54.8 x 30.5 cm

**Analogico 28 litri: + 100 °C**

Range Temperatura:  
Ambiente + 5 °C a +100 °C  
Working Access (L x W x D):  
24.1 x 44.5 x 17.8 cm  
Dimensioni (L x W x D):  
41.5 x 54.8 x 35.8 cm

**SPECIFICHE**

- Uniformità in T:  $\pm 0.2$  °C
- Stabilità in T:  $\pm 0.25$  °C



**DISTRIBUTORI ESCLUSIVI PER L'ITALIA**  
MAIL: [info@tqsrl.com](mailto:info@tqsrl.com) TEL: 0104070991

Vasca	2 Litri	2 Litri Basso	5 Litri	10 Litri	20 Litri	28 Litri	20 Litri shaker	28 Litri shaker
Range Temperatura	Ambiente + 5 °C a + 100 °C							
Riscaldatore	300 W	300 W	500 W	500 W	1000 W	1000 W	1000 W	1000 W
N. Catalogo	WA02A12E	WA2SA12E	WA05A12E	WA10A12E	WA20A12E	WA28A12E	WAS20A12E	WAS28A12E